

SELF-PROPELLED VERTICAL PERSONNEL LIFTS

| | 15DVL | 20DVL |
|--|-----------------|-----------------|
| Platform Height | 4.67 m | 5.94 m |
| Platform Capacity – Stock Picking Platform | – | – |
| Platform Capacity – Standard Platform (slide bar entry) | 230 kg | 160 kg |
| Platform Capacity – Optional Moulded Platform | 230 kg | 160 kg |
| Platform Capacity – Optional Extension Platform | 180 kg | 160 kg |
| Platform Capacity – Optional Oversized Platform | 230 kg | 160 kg |
| Platform Capacity – Optional Narrow Platform | 230 kg | 160 kg |
| Chassis Length | 1.36 m | 1.36 m |
| Overall Length – Stock Picking Platform | – | – |
| Overall Length – Standard Platform (slide bar entry) | 1.36 m | 1.36 m |
| Overall Length – Optional Moulded Platform | 1.36 m | 1.36 m |
| Overall Length – Optional Extension Platform Retracted | 1.35 m | 1.35 m |
| Overall Length – Optional Oversized Platform | 1.36 m | 1.36 m |
| Overall Length – Optional Narrow Platform | 1.36 m | 1.36 m |
| Chassis Width | 0.75 m | 0.75 m |
| Overall Width – Stock Picking Platform | – | – |
| Overall Width – Standard Platform (slide bar entry) | 0.75 m | 0.75 m |
| Overall Width – Optional Moulded Platform | 0.75 m | 0.75 m |
| Overall Width – Optional Extension Platform | 0.80 m | 0.80 m |
| Overall Width – Optional Oversized Platform | 0.75 m | 0.75 m |
| Overall Width – Optional Narrow Platform | 0.75 m | 0.75 m |
| Stowed Height | 1.98 m | 1.98 m |
| Platform Entry Height | 0.48 m | 0.48 m |
| Platform Size (L x W) – Stock Picking Platform | – | – |
| Platform Size (L x W) – Standard Platform (slide bar entry) | 0.66 m x 0.66 m | 0.66 m x 0.66 m |
| Platform Size (L x W) – Optional Moulded Platform | 0.66 m x 0.64 m | 0.66 m x 0.64 m |
| Platform Size (L x W) – Optional Extension Platform (retracted) | 0.66m x 0.66 m | 0.66m x 0.66 m |
| Platform Size (L x W) – Optional Extension Platform (fully extended) | 1.24 m x 0.66 m | 1.24 m x 0.66 m |
| Platform Size (L x W) – Optional Oversized Platform | 0.64 m x 0.71 m | 0.64 m x 0.71 m |
| Platform Size (L x W) – Optional Narrow Platform | 0.62 m x 0.56 m | 0.62 m x 0.56 m |
| Gross Weight – Stock Picking Platform | – | – |
| Gross Weight – Standard Platform (slide bar entry) | 950 kg | 950 kg |
| Gross Weight – Optional Moulded Platform | 950 kg | 950 kg |
| Gross Weight – Optional Extension Platform | 955 kg | 955 kg |
| Gross Weight – Optional Oversized Platform | 950 kg | 950 kg |
| Gross Weight – Optional Narrow Platform | 950 kg | 950 kg |
| Drive Speed - Lowered | 4 km/h | 4 km/h |
| Drive Speed - Elevated | 1 km/h | 1 km/h |
| Turning Radius | Zero | Zero |
| Gradeability | 20% | 20% |
| Distance from Platform to Wall (Standard Platform) – Over Front | 0.30 m | 0.30 m |
| Distance from Platform to Wall (Standard Platform) – Over Sides | 0.40 m | 0.40 m |
| Wheel Diameter – Front Castors | 0.20 m | 0.20 m |
| Wheel Diameter – Rear Wheels | 0.25 m | 0.25 m |

*Certain options or country standards will increase weight.
Specifications may change to meet country standards or with the addition of optional equipment.*

